

D Stride P R 9, D Stride P R 7, D Stride P R 5, D Stride P R 3


Lithium-ion behind-the-ear (BTE) direct connectivity hearing instrument series



Stride P R

SoundCore		Discover 9	Discover 7	Discover 5	Discover 3
Environmental classification	SoundNav 3.0	•	•	•	•
	Total listening environments	7	6	4	2
	Conversation in a crowd	•			
	Conversation in a small group	•	•		
	Music	•	•		
	Quiet	•	•	•	
	Noise	•	•	•	
	Conversation in quiet	•	•	•	•
	Conversation in noise	•	•	•	•
	Total streaming environments	2	2	2	2
	MediaNav speech	•	•	•	•
	MediaNav music	•	•	•	•
Sound optimization	Sound Conductor	•	•	•	•
	Speech enhancement	•	•	•	•
	Noise reduction	•	•	•	•
	Microphone features	•	•	•	•
Localization	Spatial Awareness	•	•	•	
	Personalized	•			
	Pinna Effect	•	•	•	•
Performance in challenging environments	SpeechPro	•			
	Speech Locator	•	•		
	Speech Focus	•			
	Spatial Speech	•			
	SpeechZone 2		•		
Fine-tuning channels		20	16	12	8

Fitting guides



--- Slim tube (power dome)

Available in all technology levels

Sound stabilization

- › AntiShock 2
- › Wind control
- › Feedback manager
- › Natural Sound Balance

Ease and convenience

- › Made For All direct connectivity
- › Rechargeable
- › TV Connector
- › DuoLink
- › Binaural Phone*

Fitting

- › New first fit approach
- › Automatic Adaptation Manager
- › Frequency compression 2
- › Tinnitus masker
- › MyMusic
- › Manual programs
- › IntelliVent

FLEX


- › FLEX:TRIAL
- › FLEX:UPGRADE
- › Insights
 - › Log It All
 - › Ratings (including proactive alerts)
 - › Overall satisfaction
 - › Usage

Stride P R is rated IP 68

Not all technology levels are available in all markets.


*Not available with Discover 3

ANSI 3.22 2014/IEC 60118-0: 2015 2cc coupler technical data




OSPL90

Maximum (dB SPL)	130	127
HFA - OSPL90 (dB SPL)	125	115



Full on gain (input 50 dB SPL)

Maximum (dB)	66	60
HFA - FOG (dB)	60	50



Reference test setting (RTS)

Frequency range (Hz)	100 - 6800	100 - 7000
Reference test gain (dB)	48	38
Typical battery life (h) *	18	18
Equivalent input noise at RTS (dB SPL)	19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz/3200 Hz (%)	4.0/3.0/2.0/1.0	1.0/1.0/2.0/1.0

Electromagnetic compatibility

EMC immunity by ANSI c63.19-2011 EMC, omni	M1	M1
--	----	----

Legend

- Earhook
- - - Slim Tube

Test conditions

Lithium-Ion rechargeable battery; Source: voltage 3.8 V

* Typical operating time of the rechargeable battery is based upon a combination of bluetooth streaming and regular hearing instrument usage.

The measurements obtained with a closed configuration using an HA-1 coupler (ANSI-3.7-1995).

The hearing instrument set to Unitron Truefit test settings. LLE is applied at an approximate level of 35 dB SPL.

Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.