



T Max UP Pro, T Max UP 800, T Max UP 700, T Max UP 600, T Max UP 500 675 BTE hearing aid series



Max UP

SoundCore

		T Pro	T 800	T 700	T 600	T 500
SoundNav	Music	•	•			
	Noise	•	•	•		
	Conversation in a crowd	•	•	•		
	Conversation in a small group	•	•	•		
	Conversation in quiet	•	•	•	•	
	Conversation in noise	•	•	•	•	
	Quiet	•	•	•	•	
	Total environments	7	7	6	3	AutoMic
SpeechPro	SpeechPro	•	SpeechZone2	SpeechZone		
	Speech Locator	•	•	•		
	Speech Focus	•				
	Dynamic Spatial Awareness	•				
Sound Conductor SP	Speech enhancement	•	•	•	•	•
	Noise reduction	•	•	•	•	•
	Adaptive directionality	Multiband	Multiband	Multiband	Multiband	•
Spatial Awareness	Spatial Awareness	Dynamic	Personalized	•		
	Pinna Effect	•	•	•	•	•

Sound Stabilization

	AntiShock 2	•	•	•	•	•
	Wind control	•	•	•	•	•
	Feedback manager	•	•	•	•	•
	Natural Sound Balance	•	•	•	•	•

Experience innovations

Patient insights	Log It All	•	•	•	•	•
	Patient Ratings	•	•	•	•	•
	Data logging	•	•	•	•	•
FLEX	FLEX:TRIAL	•	•	•	•	•
	FLEX:UPGRADE		•	•	•	•


Convenience

	DuoLink	•	•	•	•	•
	Telecoil and easy-t	•	•	•	•	•
	Binaural Phone	•	•	•	•	
	Easy-DAI	•	•	•	•	•

Fitting

	Power Adaptation Manager	•	•	•	•	•
	MyMusic	Binaural	Binaural	•	•	•
	Frequency compression 2	•	•	•	•	•
	Bass enhancer	•	•	•	•	•
	Tinnitus masker	•	•	•	•	•
	IntelliVent	•	•	•	•	•
	Streaming programs	•	•	•	•	•
	Manual programs	•	•	•	•	•
	NAL-NL2/NL1 and DSLv5	•	•	•	•	•
	Super Power pre-sets	•	•	•	•	•
	Fitting channels	20	20	16	10	6


Fitting guide



T Max UP is rated IP 68

Not all technology levels are available in all markets.

ANSI 3.22 2014/IEC 60118-0: 2015 2cc coupler technical data



OSPL90

Maximum (dB SPL)

139

133


139

HFA - OSPL90 (dB SPL)

124

129

133



Full on gain (input 50 dB SPL)

Maximum (dB)

82

75


82

HFA - FOG (dB)

65

69

73



Reference test setting (RTS)

Frequency range (Hz)

<100 - 5000

<100 - 5300

<100 - 5100

Reference test gain (dB)

47

52

56

Current drain at RTS (mA)

1.9

1.8

1.9

Typical battery life (h)

340

360

340

Equivalent input noise at RTS (dB SPL)

19

19


19

Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)

4.0/2.0/1.0

2.0/1.0/1.0

4.0/1.0/1.0



Induction coil sensitivity (31.6 mA/m)

HFA SPLIV/ETLS-RTLS (dB SPL/dB)

108/0

112/0


116/0

HFA MASL (1 mA/m at full on gain) (dB SPL)

95

99

103



Standard: mic at 70 dB SPL vs induction coil at 100 mA/m

--- Mic

--- Induction Coil

Electromagnetic compatibility

EMC immunity by ANSI C63.19-2011 EMC, omni/telecoil

M2/T2

M2/T2

M2/T2

Legend

— Filtered
— Unfiltered

Test conditions

Earhook: filtered; Battery size: 675; Source: voltage 1.3 V; Tubing: length 25 mm, inside diameter 1.93 mm
The hearing instrument is set to Unitron TrueFit test settings. LLE is applied at an approximate level of 35 dB SPL.
Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.
Sound pressure level of these hearing aids exceeds 132 dB SPL.
We reserve the right to change specification data without notice as improvements are introduced.